S Single Cavity Application



M MultiCavity Application

Code		C - L	1	2	T(2)	3 a 3° (-/P)	3 a 5° (-/P)	5	6
UGBE3001MA	**-/P 3/5**	C=59 L=77	UGCR3001M	REPNSP3001	S101051000J	UGBC30/P	UGBC305/P	UGBE300AR	-
UGBE3001SA	**-/P 3/5**	C=59 L=79	UGCR3001S	REPNSP3001	S101051000J	UGBC30/P	UGBC305/P	UGBE300AR	UGAS3530
UGBE3002MA	**-/P 3/5**	C=89 L=107	UGCR3002M	REPNSP3002	S101551000J	UGBC30/P	UGBC305/P	UGBE300AR	-
UGBE3002SA	**-/P 3/5**	C=89 L=109	UGCR3002S	REPNSP3002	S101551000J	UGBC30/P	UGBC305/P	UGBE300AR	UGAS3530
UGBE3003MA	**-/P 3/5**	C=119 L=137	UGCR3003M	REPNSP3003	S101551000J	UGBC30/P	UGBC305/P	UGBE300AR	-
UGBE3003SA	**-/P 3/5**	C=119 L=139	UGCR3003S	REPNSP3003	S101551000J	UGBC30/P	UGBC305/P	UGBE300AR	UGAS3530
UGBE3004MA	**-/P 3/5**	C=159 L=177	UGCR3004M	REPNSP3004	S102051000J	UGBC30/P	UGBC305/P	UGBE300AR	-
UGBE3004SA	**-/P 3/5**	C=159 L=179	UGCR3004S	REPNSP3004	S102051000J	UGBC30/P	UGBC305/P	UGBE300AR	UGAS3530

INJECTION VESTIGE: T1 OPEN FLOW NOZZLES - YES: injection on sprues - YES: intense colours, colour change and abrasive reinforcements - YES: MULTI-CAVITY applications - NO: direct moulding onto the part - NO: SINGLE CAVITY applications, for plastics with melting temperature higher than 250°C - NO: plastics leaving stringings/droolings while mould opens; in such instance you can use EP type nozzles - T2B/T2BP injection vestige.

1 = Nozzle body
(M=MultiCavity / S=Single Cavity)
2= Coil heater
T(2) = J Thermocouple
3 = Bushing
3/P = Bushing with machinable prolungation
5 = Copper ring
6 = Centering Ring
ØC = Standard 6 - On request: 7
Ød = Standard: 1,2-1,5-2,0-2,5
P = Standard: 20 - On request: 0,5 ÷ 19.9
O-RING On request





@Copyright 2026 by Emp Srl Italy - www.emp.it - info@emp.it