



Code	LT	X3	X1 min	X max	TJ	TH (x 2pcs.)	ØC
CCLDL1DQT04019	190	93	≥38	≤114	SF151551000J	REQ50604500750U	5-6-7-8-9-10
CCLDL1DQT04024	240	118	≥38	≤164	SF151551000J	REQ50605500900U	5-6-7-8-9-10
CCLDL1DQT04029	290	143	≥38	≤214	SF151551000J	REQ50606501100U	5-6-7-8-9-10
CCLDL1DQT04034	340	168	≥38	≤264	SF151551000J	REQ50607501300U	5-6-7-8-9-10
CCLDL1DQT04039	390	193	≥38	≤314	SF151551000J	REQ50608501450U	5-6-7-8-9-10
CCLDL1DQT04044	440	218	≥38	≤364	SF151551000J	REQ50609501650U	5-6-7-8-9-10
CCLDL1DQT04049	490	243	≥38	≤414	SF151551000J	REQ50610501850U	5-6-7-8-9-10

Hot runner manifold with: No.4 aligned drops and double heater circuit (No.1 heater on injection bushing side, No.1 heater on nozzle side)

No.4 drops aligned - No. 1+1 heater  
 TH = Armoured tubular heater 6 x 6 mm  
 TJ = J-type thermocouple with M4 fixing device  
 B = Min. 10 mm.(variable depending on the height of the nozzle head)  
 NOTE : centres for nozzle head of Ø26