



Code	LT	X3	X1	X	TJ	TH (x 4pcs.)	ØC
CCLDL2DQT04040	400	198	≥90	≤324	SF151551000J	REQ50604500750U	5-6-7-8-9-10
CCLDL2DQT04050	500	248	≥90	≤424	SF151551000J	REQ50605500900U	5-6-7-8-9-10
CCLDL2DQT04060	600	298	≥90	≤524	SF151551000J	REQ50606501100U	5-6-7-8-9-10
CCLDL2DQT04070	700	348	≥90	≤624	SF151551000J	REQ50607501300U	5-6-7-8-9-10
CCLDL2DQT04080	800	398	≥90	≤724	SF151551000J	REQ50608501450U	5-6-7-8-9-10
CCLDL2DQT04090	900	448	≥90	≤824	SF151551000J	REQ50609501650U	5-6-7-8-9-10
CCLDL2DQT04100	1000	498	≥90	≤924	SF151551000J	REQ50610501850U	5-6-7-8-9-10

Hot runner manifold with: No.4 aligned drops and double heater circuit (No.2 heaters on injection bushing side, No.2 heaters on nozzle side)

No.4 drops aligned - No. 2+2 heaters
 TH = Armoured tubular heater 6 x 6 mm
 TJ = J-type thermocouple with M4 fixing device
 B = Min. 10 mm.(variable depending on the height of the nozzle head)
 NOTE : centres for nozzle head of Ø26