



Code	LT	X3	X1 min	X max	TJ	TH (x 4pcs.)	ØC
CCLDL2DQT08040	400	198	>=50	<=324	SF151551000J	REQ50604500750U	5-6-7-8
CCLDL2DQT08050	500	248	>=50	<=424	SF151551000J	REQ50605500900U	5-6-7-8
CCLDL2DQT08060	600	298	>=50	<=524	SF151551000J	REQ50606501100U	5-6-7-8
CCLDL2DQT08070	700	348	>=50	<=624	SF151551000J	REQ50607501300U	5-6-7-8
CCLDL2DQT08080	800	398	>=50	<=724	SF151551000J	REQ50608501450U	5-6-7-8
CCLDL2DQT08090	900	448	>=50	<=824	SF151551000J	REQ50609501650U	5-6-7-8
CCLDL2DQT08100	1000	498	>=50	<=924	SF151551000J	REQ50610501850U	5-6-7-8

Hot runner manifold with: No.8 aligned drops and double heater circuit (No.1 heater on injection bushing side, No.1 heater on nozzle side)

No.8 drops aligned - No. 2+2 heaters  
 TH = Armoured tubular heater 6 x 6 mm  
 TJ = J-type thermocouple with M4 fixing device  
 B = Min. 10 mm.(variable depending on the height of the nozzle head)  
 NOTE : centres for nozzle head of Ø26