



Code	LT	X3	X1 min	X max	TJ	TH (x 2pcs.)	ØC
CCLDR1DQT06024	240	118	≥38	≤164	SF151551000J	REQ50605500900T	5-6-7-8
CCLDR1DQT06029	290	142	≥38	≤214	SF151551000J	REQ50606501100T	5-6-7-8
CCLDR1DQT06034	340	168	≥38	≤264	SF151551000J	REQ50607501300T	5-6-7-8
CCLDR1DQT06039	390	193	≥38	≤314	SF151551000J	REQ50608501450T	5-6-7-8
CCLDR1DQT06044	440	218	≥38	≤364	SF151551000J	REQ50609501650T	5-6-7-8
CCLDR1DQT06049	490	243	≥38	≤414	SF151551000J	REQ50610501850T	5-6-7-8

Hot runner manifold with: No.6 aligned drops and double heater circuit (No.1 heater on injection bushing side, No.1 heater on nozzle side)

No.6 drops aligned - No. 1+1 heater
 TH = Armoured tubular heater 6 x 6 mm
 TJ = J-type thermocouple with M4 fixing device
 B = Min. 10 mm.(variable depending on the height of the nozzle head)
 NOTE : X distances calculated for the heads of the nozzle Ø26