



| Code | LT | X3 | X1 min | X max | TJ | TH (x 4pcs.) | ØC |
|----------------|------|-----|--------|-------|--------------|-----------------|--------------|
| CCLDR2DQT04040 | 400 | 198 | >=90 | <=324 | SF151551000J | REQ50604500750T | 5-6-7-8-9-10 |
| CCLDR2DQT04050 | 500 | 248 | >=90 | <=424 | SF151551000J | REQ50605500900T | 5-6-7-8-9-10 |
| CCLDR2DQT04060 | 600 | 298 | >=90 | <=524 | SF151551000J | REQ50606501100T | 5-6-7-8-9-10 |
| CCLDR2DQT04070 | 700 | 348 | >=90 | <=624 | SF151551000J | REQ50607501300T | 5-6-7-8-9-10 |
| CCLDR2DQT04080 | 800 | 398 | >=90 | <=724 | SF151551000J | REQ50608501450T | 5-6-7-8-9-10 |
| CCLDR2DQT04090 | 900 | 448 | >=90 | <=824 | SF151551000J | REQ50609501650T | 5-6-7-8-9-10 |
| CCLDR2DQT04100 | 1000 | 498 | >=90 | <=924 | SF151551000J | REQ50610501850T | 5-6-7-8-9-10 |

Hot runner manifold with: No.4 aligned drops and double heater circuit (No.2 heaters on injection bushing side, No.2 heaters on nozzle side)

No.4 drops aligned - No. 2+2 heaters
 TH = Armoured tubular heater 6 x 6 mm
 TJ = J-type thermocouple with M4 fixing device
 B = Min. 10 mm.(variable depending on the height of the nozzle head)
 NOTE : centres for nozzle head of Ø26