



Code	LT	X3	X1 min	X max	TJ	TH (x 4pcs.)	ØC
CCLDR2DQT06040	400	198	≥90	≤324	SF151551000J	REQ50604500750T	5-6-7-8
CCLDR2DQT06050	500	248	≥90	≤424	SF151551000J	REQ50605500900T	5-6-7-8
CCLDR2DQT06060	600	298	≥90	≤524	SF151551000J	REQ50606501100T	5-6-7-8
CCLDR2DQT06070	700	348	≥90	≤624	SF151551000J	REQ50607501300T	5-6-7-8
CCLDR2DQT06080	800	398	≥90	≤724	SF151551000J	REQ50608501450T	5-6-7-8
CCLDR2DQT06090	900	448	≥90	≤824	SF151551000J	REQ50609501650T	5-6-7-8
CCLDR2DQT06100	1000	498	≥90	≤924	SF151551000J	REQ50610501850T	5-6-7-8

Hot runner manifold with: No.6 aligned drops and double heater circuit (No.2 heaters on injection bushing side, No.2 heaters on nozzle side)

No.6 drops aligned - No. 2+2 heaters
 TH = Armoured tubular heater 6 x 6 mm
 TJ = J-type thermocouple with M4 fixing device
 B = Min. 10 mm.(variable depending on the height of the nozzle head)
 NOTE : centres for nozzle head of Ø26