



Code	LT	X3	X1	X max	TJ	TH (x 4pcs.)	ØC
CCLDR2DQT08040	400	198	>=90	<=324	SF151551000J	REQ50604500750T	5-6-7-8
CCLDR2DQT08050	500	248	>=90	<=424	SF151551000J	REQ50605500900T	5-6-7-8
CCLDR2DQT08060	600	298	>=90	<=524	SF151551000J	REQ50606501100T	5-6-7-8
CCLDR2DQT08070	700	348	>=90	<=624	SF151551000J	REQ50607501300T	5-6-7-8
CCLDR2DQT08080	800	398	>=90	<=724	SF151551000J	REQ50608501450T	5-6-7-8
CCLDR2DQT08090	900	448	>=90	<=824	SF151551000J	REQ50609501650T	5-6-7-8
CCLDR2DQT08100	1000	498	>=90	<=924	SF151551000J	REQ50610501850T	5-6-7-8

Hot runner manifold with: No.8 aligned drops and double heater circuit (No.2 heaters on injection bushing side, No.2 heaters on nozzle side)

No.8 drops aligned - No. 2+2 heaters
 TH = Armoured tubular heater 6 x 6 mm
 TJ = J-type thermocouple with M4 fixing device
 B = Min. 10 mm.(variable depending on the height of the nozzle head)
 NOTE : centres for nozzle head of Ø26