



Code	ØC	X3	X min	Y min	TJ	TH (x 4pcs.)	X * Y min ÷ max
CCLH2AQT08012	5 ÷ 8	TEC	81	98	SF151551000J	REQ506 SV W DIS	÷ 12.769
CCLH2AQT08022	5 ÷ 8	TEC	81	98	SF151551000J	REQ506 SV W DIS	12.770 ÷ 21.904
CCLH2AQT08033	5 ÷ 8	TEC	81	98	SF151551000J	REQ506 SV W DIS	21.905 ÷ 33.856
CCLH2AQT08047	5 ÷ 8	TEC	81	98	SF151551000J	REQ506 SV W DIS	33.857 ÷ 47.961
CCLH2AQT08064	5 ÷ 8	TEC	81	98	SF151551000J	REQ506 SV W DIS	47.962 ÷ 64.516
CCLH2AQT08083	5 ÷ 8	TEC	81	98	SF151551000J	REQ506 SV W DIS	64.517 ÷ 83.640
CCLH2AQT08105	5 ÷ 8	TEC	81	98	SF151551000J	REQ506 SV W DIS	83.640 ÷ 105.625
CCLH2AQT08129	5 ÷ 8	TEC	81	98	SF151551000J	REQ506 SV W DIS	105.626 ÷ 129.600
CCLH2AQT08156	5 ÷ 8	TEC	81	98	SF151551000J	REQ506 SV W DIS	129.601 ÷ 156.025
CCLH2AQT08202	5 ÷ 8	TEC	81	98	SF151551000J	REQ506 SV W DIS	156.026 ÷ 202.500

Hot runner manifold with: No.8 drops on two rows and double heater circuit (No.2 heaters on injection bushing side, No.2 heaters on nozzle side)

No.8 drops on two rows - No.2+2 heaters  
 TH = Armoured tubular heater 6 x 6 mm  
 TJ = J-type thermocouple with M4 fixing device  
 B = Min. 10 mm.(variable depending on the height of the nozzle head)  
 L Standard = 66 mm  
 NOTE : centres for nozzle head of Ø26  
 TEC = Please ask EMP Technical Office