



Codice	ØC	X3	X min	Y min	TJ	TH (x 4pcs.)	X * Y min ÷ max
CCLP2AQT04012	5 ÷ 10	TEC	54	80	SF151551000J	REQ506 SV W DIS	÷ 12.769
CCLP2AQT04022	5 ÷ 10	TEC	54	80	SF151551000J	REQ506 SV W DIS	12.770 ÷ 21.904
CCLP2AQT04033	5 ÷ 10	TEC	54	80	SF151551000J	REQ506 SV W DIS	21.905 ÷ 33.856
CCLP2AQT04047	5 ÷ 10	TEC	54	80	SF151551000J	REQ506 SV W DIS	33.857 ÷ 47.961
CCLP2AQT04064	5 ÷ 10	TEC	54	80	SF151551000J	REQ506 SV W DIS	47.962 ÷ 64.516
CCLP2AQT04083	5 ÷ 10	TEC	54	80	SF151551000J	REQ506 SV W DIS	64.517 ÷ 83.640
CCLP2AQT04105	5 ÷ 10	TEC	54	80	SF151551000J	REQ506 SV W DIS	83.640 ÷ 105.625
CCLP2AQT04129	5 ÷ 10	TEC	54	80	SF151551000J	REQ506 SV W DIS	105.626 ÷ 129.600
CCLP2AQT04156	5 ÷ 10	TEC	54	80	SF151551000J	REQ506 SV W DIS	129.601 ÷ 156.025
CCLP2AQT04202	5 ÷ 10	TEC	54	80	SF151551000J	REQ506 SV W DIS	156.026 ÷ 202.500

Hot runner manifold with: No.4 drops on two rows and double heater circuit (No.2 heaters on injection bushing side, No.2 heaters on nozzle side)

No.4 drops on two rows - No.2+2 heaters
 TH = Armoured tubular heater 6 x 6 mm
 TJ = J-type thermocouple with M4 fixing device
 B = Min. 10 mm.(variable depending on the height of the nozzle head)
 NOTE : centres for nozzle head of Ø26
 TEC = Please ask EMP Technical Office