



Code	ØC	X3	X,Y min	X,Y max	TJ	TH (x 2pcs.)	X * Y min ÷ max
CCXS1DQT04004	5 ÷ 13	TEC	>=27	<=68	SF151551000J	REQ506 SV W DIS+	÷ 4.624
CCXS1DQT04007	5 ÷ 13	TEC	>68	<=85	SF151551000J	REQ506 SV W DIS+	4.625 ÷ 7.225
CCXS1DQT04012	5 ÷ 13	TEC	>85	<=113	SF151551000J	REQ506 SV W DIS+	7.226 ÷ 12.769
CCXS1DQT04022	5 ÷ 13	TEC	>113	<=148	SF151551000J	REQ506 SV W DIS+	12.770 ÷ 21.904
CCXS1DQT04033	5 ÷ 13	TEC	>148	<=184	SF151551000J	REQ506 SV W DIS+	21.905 ÷ 33.856

Hot runner manifold with: No.4 drops on two rows and double heater circuit (No.1 heater on injection bushing side, No.1 heater on nozzle side)

No.4 drops on two rows - No.1+1 heater
 TH = Armoured tubular heater 6 x 6 mm
 TJ = J-type thermocouple with M4 fixing device
 B = Min. 10 mm.(variable depending on the height of the nozzle head)
 L Standard = 66 mm
 NOTE : centres for nozzle head of Ø26
 TEC = Please ask EMP Technical Office