



Code	ØC	X3	X,Y min	X,Y max	TJ	TH (x 4pcs.)	X * Y min ÷ max
CCXS2DQT04012	5 ÷ 13	TEC	>=85	<=113	SF151551000J	REQ506 SV W DIS	7.226 ÷ 12.769
CCXS2DQT04022	5 ÷ 13	TEC	>113	<=148	SF151551000J	REQ506 SV W DIS	12.770 ÷ 21.904
CCXS2DQT04033	5 ÷ 13	TEC	>148	<=184	SF151551000J	REQ506 SV W DIS	21.905 ÷ 33.856
CCXS2DQT04047	5 ÷ 13	TEC	>184	<=219	SF151551000J	REQ506 SV W DIS	33.857 ÷ 47.961
CCXS2DQT04064	5 ÷ 13	TEC	>219	<=254	SF151551000J	REQ506 SV W DIS	47.962 ÷ 64.516
CCXS2DQT04083	5 ÷ 13	TEC	>254	<=289	SF151551000J	REQ506 SV W DIS	64.517 ÷ 83.640
CCXS2DQT04105	5 ÷ 13	TEC	>289	<=325	SF151551000J	REQ506 SV W DIS	83.641 ÷ 105.625
CCXS2DQT04129	5 ÷ 13	TEC	>325	<=360	SF151551000J	REQ506 SV W DIS	105.626 ÷ 129.600
CCXS2DQT04156	5 ÷ 13	TEC	>360	<=395	SF151551000J	REQ506 SV W DIS	129.601 ÷ 156.025

Hot runner manifold with: No.4 drops on two rows and double heater circuit (No.2 heaters on injection bushing side, No.2 heaters on nozzle side)

No.4 drops on two rows - No.2+2 heaters  
 TH = Armoured tubular heater 6 x 6 mm  
 TJ = J-type thermocouple with M4 fixing device  
 B = Min. 10 mm.(variable depending on the height of the nozzle head)  
 L Standard = 66 mm  
 NOTE : centres for nozzle head of Ø26  
 TEC = Please ask EMP Technical Office