



DATI TECNICI / TECHNICAL DATA	
Ø	3/4" (19,05mm) - 0,06 / - 0,10 mm
L	< 100 mm ± 2mm
	> 100 mm ± 2%
W	+ 5% / - 10%

TCJ on demand

FLEX	Ø	L	Watt
1900076A0300X	3/4" (19,05mm)	3" (76,2mm)	300
1900076A0400X	3/4" (19,05mm)	3" (76,2mm)	400
1900076A0500X	3/4" (19,05mm)	3" (76,2mm)	500
1270102A0400X	3/4" (19,05mm)	4" (101,6mm)	400
1270102A0400X	3/4" (19,05mm)	4" (101,6mm)	600
1270102A0400X	3/4" (19,05mm)	4" (101,6mm)	800
1270102A0400X	3/4" (19,05mm)	4" (101,6mm)	1000
1270127A0400X	3/4" (19,05mm)	5" (127mm)	400
1270127A0500X	3/4" (19,05mm)	5" (127mm)	500
1270127A1000X	3/4" (19,05mm)	5" (127mm)	1000
1270127A1500X	3/4" (19,05mm)	5" (127mm)	1500
1270152A0400X	3/4" (19,05mm)	6" (152,4mm)	400
1270152A0600X	3/4" (19,05mm)	6" (152,4mm)	600
1270152A1000X	3/4" (19,05mm)	6" (152,4mm)	1000
1270152A1500X	3/4" (19,05mm)	6" (152,4mm)	1500
1270203A0500X	3/4" (19,05mm)	8" (203,2mm)	500
1270203A0600X	3/4" (19,05mm)	8" (203,2mm)	600
1270203A1000X	3/4" (19,05mm)	8" (203,2mm)	1000
1270203A2000X	3/4" (19,05mm)	8" (203,2mm)	2000
1270254A0800X	3/4" (19,05mm)	10" (254mm)	800
1270254A1000X	3/4" (19,05mm)	10" (254mm)	1000
1270254A2000X	3/4" (19,05mm)	10" (254mm)	2000
1270305A0800X	3/4" (19,05mm)	12" (304,8mm)	800
1270305A1000X	3/4" (19,05mm)	12" (304,8mm)	1000
1270305A1500X	3/4" (19,05mm)	12" (304,8mm)	1500
1270305A2000X	3/4" (19,05mm)	12" (304,8mm)	2000
1270305A2500X	3/4" (19,05mm)	12" (304,8mm)	2500
1270356A1500X	3/4" (19,05mm)	14" (355,6mm)	1500
1270356A2000X	3/4" (19,05mm)	14" (355,6mm)	2000
1270356A2500X	3/4" (19,05mm)	14" (355,6mm)	2500
1270356A3000X	3/4" (19,05mm)	14" (355,6mm)	3000
1270356A3500X	3/4" (19,05mm)	14" (355,6mm)	3500