



**M** MultiCavity Application

Code	C - L	1	2	T(2)	4/1	*
UGDL3511MA	C=40 L=55	UGDL341C	REPNSPDL31	S151051000J	UGDL3500P	Z=0,14
UGDL3512MA	C=60 L=75	UGDL342C	REPNSPDL32	S151051000J	UGDL3500P	Z=0,19
UGDL3513MA	C=80 L=95	UGDL343C	REPNSPDL33	S151051000J	UGDL3500P	Z=0,24
UGDL3514MA	C=100 L=115	UGDL344C	REPNSPDL34	S151551000J	UGDL3500P	Z=0,29

INJECTION VESTIGE: T3 DIRECT INJECTION NOZZLES , MULTI-CAVITY APPLICATION ONLY - YES: frequent color change - YES: intense colours - NO: plastics that leave stringings / droolings while mould opens - NO: plastics with melting temperature higher than 270°C - NO: abrasive reinforcements

- 1 = Nozzle body
- 2 = Coil heater
- T(2) = J Termocouple
- 4 = Cu-Be Tip
- ØC = Standard: 6
- Ød = standard: 1,5 ÷ 1,7 - on request 0,6 ÷ 3,2
- \* = Elongation (nozzle temperature - mould temperature = 200°C)
- O-Ring on request

