



Code	LT	X3	X1 min	X max	N	TJ	N	TH (x 2pcs.)	ØC
CCLDR1DQT04019	190	93	>=38	<=114	2	SF151551000J	2	REQ50604500750T	5-6-7-8-9-10
CCLDR1DQT04024	240	118	>=38	<=164	2	SF151551000J	2	REQ50605500900T	5-6-7-8-9-10
CCLDR1DQT04029	290	143	>=38	<=214	2	SF151551000J	2	REQ50606501100T	5-6-7-8-9-10
CCLDR1DQT04034	340	168	>=38	<=264	2	SF151551000J	2	REQ50607501300T	5-6-7-8-9-10
CCLDR1DQT04039	390	193	>=38	<=314	2	SF151551000J	2	REQ50608501450T	5-6-7-8-9-10
CCLDR1DQT04044	440	218	>=38	<=364	2	SF151551000J	2	REQ50609501650T	5-6-7-8-9-10
CCLDR1DQT04049	490	243	>=38	<=414	2	SF151551000J	2	REQ50610501850T	5-6-7-8-9-10

Hot runner manifold with: No.4 aligned drops and double heater circuit (No.1 heater on injection bushing side, No.1 heater on nozzle side)

No.4 drops aligned - No. 1+1 heater  
 TH = Armoured tubular heater 6 x 6 mm  
 TJ = J-type thermocouple with M4 fixing device  
 B = Min. 10 mm.(variable depending on the height of the nozzle head)  
 NOTE : centres for nozzle head of Ø26