



**M** MultiCavity Application

Code	L - C	1	2	T(2)	3	4 - 0/1	7
UGET4001A0	L=74 C=54	UGCR4001M	REPNSP4001	S151051000J	UGBC440	UGPU45TZ	UGACOR11
UGET4001A1	L=74 C=54	UGCR4001M	REPNSP4001	S151051000J	UGBC440	UGPU45CU	UGACOR11
UGET4002A0	L=104 C=84	UGCR4002M	REPNSP4002	S151051000J	UGBC440	UGPU45TZ	UGACOR11
UGET4002A1	L=104 C=84	UGCR4002M	REPNSP4002	S151051000J	UGBC440	UGPU45CU	UGACOR11
UGET4003A0	L=134 C=114	UGCR4003M	REPNSP4003	S151551000J	UGBC440	UGPU45TZ	UGACOR11
UGET4003A1	L=134 C=114	UGCR4003M	REPNSP4003	S151551000J	UGBC440	UGPU45CU	UGACOR11
UGET4004A0	L=184 C=164	UGCR4004M	REPNSP4004	S152051000J	UGBC440	UGPU45TZ	UGACOR11
UGET4004A1	L=184 C=164	UGCR4004M	REPNSP4004	S152051000J	UGBC440	UGPU45CU	UGACOR11
UGET4005A0	L=234 C=214	UGCR4505M	REPNSP4005	S152551000J	UGBC440	UGPU45TZ	UGACOR11
UGET4005A1	L=234 C=214	UGCR4505M	REPNSP4005	S152551000J	UGBC440	UGPU45CU	UGACOR11

INJECTION VESTIGE: T6 Direct injection nozzles for MULTI CAVITY applications. With needle valve activated by INNER PNEUMATIC PISTON. Suitable for: -excellent aesthetic finish of the injection point - intense colours and colour change - abrasive reinforcements (choose the 4/0 tip)

- 1 = Nozzle body
- 2 = Coil heater
- T2= J thermocouple
- 3 = Opened bushing
- 4/0 = Abrasive charges tip
- 4/1 = Cu-Be tip
- 7 = O-RING

- 9 = UGET04UGU-DLC Needle valve sealing with wear-resistant coating
- 10 = UGET04TT-DLC Needle valve Ø4 with wear-resistant coating (length to be defined)
- 11 = UGTL550K Pneumatic piston Kit (piston UGTL550PP-XB6 + needle valve support UGET04ST-M8 + N.2 fittings UGTL550RC and spacers N.2 UGTL550PD+ N.2 UGTL550SP)

ØC = Standard : 9 - On request: 10  
 Ød = Standard: 1,0 ÷ 3,0

