



$$Z = C * (12.7 * 10^{-6}) * \Delta T$$

M MultiCavity Application

Code	L - C	1	2	T(2)	3 -/3P	4/0 - 4/1	7
UGET4101A 0/1	L=74 C=54	UGCR4001M	REPNSP4001	S151051000J	UGBC45	UGPU45TZ UGPU45CU	UGACOR11
UGET4101AP 0/1	L=74 C=54	UGCR4001M	REPNSP4001	S151051000J	UGBC45P	UGPU45TZ UGPU45CU	UGACOR11
UGET4102A 0/1	L=104 C=84	UGCR4002M	REPNSP4002	S151051000J	UGBC45	UGPU45TZ UGPU45CU	UGACOR11
UGET4102AP 0/1	L=104 C=84	UGCR4002M	REPNSP4002	S151051000J	UGBC45P	UGPU45TZ UGPU45CU	UGACOR11
UGET4103A 0/1	L=134 C=114	UGCR4003M	REPNSP4003	S151551000J	UGBC45	UGPU45TZ UGPU45CU	UGACOR11
UGET4103AP 0/1	L=134 C=114	UGCR4003M	REPNSP4003	S151551000J	UGBC45P	UGPU45TZ UGPU45CU	UGACOR11
UGET4104A 0/1	L=184 C=164	UGCR4004M	REPNSP4004	S152051000J	UGBC45	UGPU45TZ UGPU45CU	UGACOR11
UGET4104AP 0/1	L=184 C=164	UGCR4004M	REPNSP4004	S152051000J	UGBC45P	UGPU45TZ UGPU45CU	UGACOR11
UGET4105A 0/1	L=234 C=214	UGCR4005M	REPNSP4005	S152551000J	UGBC45	UGPU45TZ UGPU45CU	UGACOR11
UGET4105AP 0/1	L=234 C=214	UGCR4005M	REPNSP4005	S152551000J	UGBC45P	UGPU45TZ UGPU45CU	UGACOR11

INJECTION VESTIGE: T6B / T6BP Direct injection nozzles for MULTI CAVITY applications. With needle valve activated by OUTER PNEUMATIC PISTON. Suitable for: - excellent aesthetic finish of the injection point (TBP6 only suitable for injection on sprues) - intense colours and colour change - abrasive reinforcements (choose the 4/0 tip)

- 1 = Nozzle body
- 2 = Coil heater
- T2= J thermocouple
- 3 = Closed bushing
- 3/P = Bushing with machinable prolongation
- 4/0 = Abrasive charges tip
- 4/1 = Cu-Be tip
- 7 = O-RING

- 9 = UGET04UGU-DLC Needle valve sealing with wear-resistant coating
- 10 = UGET04TT-DLC Needle valve Ø4 with wear-resistant coating (length to be defined)
- 11= UGTL550K Pneumatic piston Kit (piston UGTL550PP-XB6 + needle valve support UGET04ST-M8 + N.2 fittings UGTL550RC and spacers N.2 UGTL550PD+ N.2 UGTL550SP)

ØC = Standard : 9 - On request: 10
 Ød = Standard: 1,0 ÷ 3,0
 P = Standard: 25 - On request: 0,5 ÷ 24,9

