



$$Z=C*(12.7*10^{-6})^{*}\blacktriangle T$$

M MultiCavity Application

Code	L - C	1	2	T(2)	3 - 3/P	4/0 - 4/1	7	
UGET4111A 0/1	L=74 C=54	UGCR4001M	REPNSP4001	S151051000J	UGBC45	UGPU45TZ	UGPU45CU	UGACOR11
UGET4111AP 0/1	L=74 C=54	UGCR4001M	REPNSP4001	S151051000J	UGBC45P	UGPU45TZ	UGPU45CU	UGACOR11
UGET4112A 0/1	L=104 C=84	UGCR4002M	REPNSP4002	S151051000J	UGBC45	UGPU45TZ	UGPU45CU	UGACOR11
UGET4112AP 0/1	L=104 C=84	UGCR4002M	REPNSP4002	S151051000J	UGBC45P	UGPU45TZ	UGPU45CU	UGACOR11
UGET4113A 0/1	L=134 C=114	UGCR4003M	REPNSP4003	S151551000J	UGBC45	UGPU45TZ	UGPU45CU	UGACOR11
UGET4113AP 0/1	L=134 C=114	UGCR4003M	REPNSP4003	S151551000J	UGBC45P	UGPU45TZ	UGPU45CU	UGACOR11
UGET4114A 0/1	L=184 C=164	UGCR4004M	REPNSP4004	S152051000J	UGBC45	UGPU45TZ	UGPU45CU	UGACOR11
UGET4114AP 0/1	L=184 C=164	UGCR4004M	REPNSP4004	S152051000J	UGBC45P	UGPU45TZ	UGPU45CU	UGACOR11
UGET4115A 0/1	L=234 C=214	UGCR4005M	REPNSP4005	S152551000J	UGBC45	UGPU45TZ	UGPU45CU	UGACOR11
UGET4115AP 0/1	L=234 C=214	UGCR4005M	REPNSP4005	S152551000J	UGBC45P	UGPU45TZ	UGPU45CU	UGACOR11

INJECTION VESTIGE: T6B / T6BP Direct injection nozzles for MULTI CAVITY applications. With needle valve activated by OUTER HYDRAULIC PISTON. Suitable for: - excellent aesthetic finish of the injection point (T6BP only suitable for injection on sprues) - intense colours and colour change - abrasive reinforcements (choose the 4/0 tip)

- 1 = Nozzle body
- 2 = Coil heater
- T2= J thermocouple
- 3 = Closed bushing
- 3/P = Bushing with machinable prolongation
- 4/0 = Abrasive charges tip
- 4/1 = Cu-Be tip
- 7 = O-RING

- 9 = Needle valve sealing (wear-resistant coating)
- 10 = Needle valve Ø5 (wear-resistant coating)
- *Length to be defined
- 11= Hydraulic piston kit (piston UGTLRUPIW + needle valve support UGET04ST-M10 + N.2 fittings UGTLRUPIRC)
- ØC = Standard : 12 - On request: 13
- Ød = Standard: 2,0 ÷ 4,0
- P = Standard: 25 - On request: 0,5 ÷ 24,9

