



M MultiCavity Application

Code	L - C	1	2	T(2)	3	4 - 0/1	7
UGET5001A0	L=74 C=54	UGCR5001M	REPNSP5001	S151051000J	UGBC550	UGPU55TZ	UGACOR14
UGET5001A1	L=74 C=54	UGCR5001M	REPNSP5001	S151051000J	UGBC550	UGPU55CU	UGACOR14
UGET5002A0	L=104 C=84	UGCR5002M	REPNSP5002	S151051000J	UGBC550	UGPU55TZ	UGACOR14
UGET5002A1	L=104 C=84	UGCR5002M	REPNSP5002	S151051000J	UGBC550	UGPU55CU	UGACOR14
UGET5003A0	L=134 C=144	UGCR5003M	REPNSP5003	S151551000J	UGBC550	UGPU55TZ	UGACOR14
UGET5003A1	L=134 C=144	UGCR5003M	REPNSP5003	S151551000J	UGBC550	UGPU55CU	UGACOR14
UGET5004A0	L=184 C=164	UGCR5004M	REPNSP5004	S152051000J	UGBC550	UGPU55TZ	UGACOR14
UGET5004A1	L=184 C=164	UGCR5004M	REPNSP5004	S152051000J	UGBC550	UGPU55CU	UGACOR14
UGET5005A0	L=234 C=214	UGCR5005M	REPNSP5005	S152551000J	UGBC550	UGPU55TZ	UGACOR14
UGET5005A1	L=234 C=214	UGCR5005M	REPNSP5005	S152551000J	UGBC550	UGPU55CU	UGACOR14

INJECTION VESTIGE: T6 Direct injection nozzles for SINGLE and MULTI CAVITY applications. With needle valve activated by INNER PNEUMATIC PISTON. Suitable for: - making gate vestige nearly invisible - intense colours and colour change - abrasive reinforcements (choose the 4/0 tip)

- 1 = Nozzle body
- 2 = Coil heater
- T2= J thermocouple
- 3 = Opened bushing
- 4/0 = Abrasive charges tip
- 4/1 = Cu-Be tip
- 7 = O-RING

- 9 = UGET05UGU-DLC Needle valve sealing with wear-resistant coating
- 10 = UGET05TT-DLC Needle valve $\phi 5$ with wear-resistant coating (length to be defined)
- 11 = UGTL720K Pneumatic piston Kit (piston UGTL720PP-XB6 + needle valve support UGET05ST-M8 + No.2 fittings UGTL720RC and spacers No.2 UGTL550PD+ No.2 UGTL550SP)

ϕC = Standard : 12 - On request: 13
 ϕd = Standard: 2,0 ÷ 4,0

