



M MultiCavity Application

Code	L - C	1	2	T(2)	3 -/3P	4/0 - 4/1	7	
UGET5111A 0/1	L=74 C=54	UGCR5001M	REPNSP5001	S151051000J	UGBC55	UGPU55TZ	UGPU55CU	UGACOR14
UGET5111AP 0/1	L=74 C=54	UGCR5001M	REPNSP5001	S151051000J	UGBC55P	UGPU55TZ	UGPU55CU	UGACOR14
UGET5112A 0/1	L=104 C=84	UGCR5002M	REPNSP5002	S151051000J	UGBC55	UGPU55TZ	UGPU55CU	UGACOR14
UGET5112AP 0/1	L=104 C=84	UGCR5002M	REPNSP5002	S151051000J	UGBC55P	UGPU55TZ	UGPU55CU	UGACOR14
UGET5113A 0/1	L=134 C=114	UGCR5003M	REPNSP5003	S151551000J	UGBC55	UGPU55TZ	UGPU55CU	UGACOR14
UGET5113AP 0/1	L=134 C=114	UGCR5003M	REPNSP5003	S151551000J	UGBC55P	UGPU55TZ	UGPU55CU	UGACOR14
UGET5114A 0/1	L=184 C=164	UGCR5004M	REPNSP5004	S152051000J	UGBC55	UGPU55TZ	UGPU55CU	UGACOR14
UGET5114AP 0/1	L=184 C=164	UGCR5004M	REPNSP5004	S152051000J	UGBC55P	UGPU55TZ	UGPU55CU	UGACOR14
UGET5115A 0/1	L=234 C=214	UGCR5005M	REPNSP5005	S152551000J	UGBC55	UGPU55TZ	UGPU55CU	UGACOR14
UGET5115AP 0/1	L=234 C=214	UGCR5005M	REPNSP5005	S152551000J	UGBC55P	UGPU55TZ	UGPU55CU	UGACOR14

INJECTION VESTIGE: T6B / T6BP Direct injection nozzles for MULTI CAVITY applications. With needle valve activated by OUTER HYDRAULIC PISTON. Suitable for: - excellent aesthetic finish of the injection point (T6BP only suitable for injection on sprues) - intense colours and colour change - abrasive reinforcements (choose the 4/0 tip)

- 1 = Nozzle body
- 2 = Coil heater
- T2= J thermocouple
- 3 = Closed bushing
- 3/P = Bushing with machinable prolongation
- 4/0 = Abrasive charges tip
- 4/1 = Cu-Be tip
- 7 = O-RING

- 9 = UGET05UGU-DLC Needle valve sealing with wear-resistant coating
- 10 = UGET05TT-DLC Needle valve Ø5 with wear-resistant coating (length to be defined)
- 11= UGTLRUPIK5 Hydraulic piston kit (piston UGTLRUPIW + needle valve support UGET05ST-M10 + No.2 fittings UGTLRUPIC)

ØC = Standard : 12 - On request: 13
 Ød = Standard: 2,0 ÷ 4,0
 P = Standard: 25 - On request: 0,5 ÷ 24.9

