



**M** MultiCavity Application

Codice	L - C	1	2	T(2)	3 - 3/P	4/0 - 4/1	7	
UGET6112A 0/1	L=79 C=54	UGCR6002M	REPNSP6002	S151051000J	UGBC65	UGPU65TZ	UGPU65CU	UGACOR17
UGET6112AP 0/1	L=79 C=54	UGCR6002M	REPNSP6002	S151051000J	UGBC65P	UGPU65TZ	UGPU65CU	UGACOR17
UGET6113A 0/1	L=99 C=74	UGCR6003M	REPNSP6003	S151551000J	UGBC65	UGPU65TZ	UGPU65CU	UGACOR17
UGET6113AP 0/1	L=99 C=74	UGCR6003M	REPNSP6003	S151551000J	UGBC65P	UGPU65TZ	UGPU65CU	UGACOR17
UGET6114A 0/1	L=119 C=94	UGCR6004M	REPNSP6004	S151051000J	UGBC65	UGPU65TZ	UGPU65CU	UGACOR17
UGET6114AP 0/1	L=119 C=94	UGCR6004M	REPNSP6004	S151051000J	UGBC65P	UGPU65TZ	UGPU65CU	UGACOR17
UGET6115A 0/1	L=139 C=114	UGCR6005M	REPNSP6005	S151551000J	UGBC65	UGPU65TZ	UGPU65CU	UGACOR17
UGET6115AP 0/1	L=139 C=114	UGCR6005M	REPNSP6005	S151551000J	UGBC65P	UGPU65TZ	UGPU65CU	UGACOR17
UGET6117A 0/1	L=189 C=164	UGCR6007M	REPNSP6007	S152051000J	UGBC65	UGPU65TZ	UGPU65CU	UGACOR17
UGET6117AP 0/1	L=189 C=164	UGCR6007M	REPNSP6007	S152051000J	UGBC65P	UGPU65TZ	UGPU65CU	UGACOR17

INJECTION VESTIGE: T6B / T6BP Direct injection nozzles for MULTI CAVITY applications. With needle valve activated by OUTER HYDRAULIC PISTON. Suitable for: - excellent aesthetic finish of the injection point (T6BP only suitable for injection on sprues) - intense colours and colour change - abrasive reinforcements (choose the 4/0 tip)

- 1 = Nozzle body
- 2 = Coil heater
- T2= J thermocouple
- 3 = Opened bushing
- 3/P = Bushing with machinable prolongation
- 4/0 = Abrasive charges tip
- 4/1 = Cu-Be tip
- 7 = O-RING

- 9 = UGET06UGU-DLC Needle valve sealing with wear-resistant coating
- 10 = UGET06TT-DLC Needle valve Ø6 with wear-resistant coating (length to be defined)
- 11= UGTLRUIK6 Hydraulic piston kit (piston UGTLRUIPW + needle valve support UGET06ST-M10 + No.2 fittings UGTLRUIRC)

ØC = Standard : 16 - On request: 17  
 Ød = Standard: 3,0 ÷ 5,0  
 P = Standard: 25 - On request: 0,5 ÷ 24,9

