



DATI TECNICI / TECHNICAL DATA		
Ø	6,50 mm	- 0,03 / - 0,05 mm
L	< 100 mm	± 2mm
	> 100 mm	± 2%
W	+ 5% / - 10%	
V	230	

FLEX	TCJ	Ø	L	V.230 Watt	FLEX	TCJ	Ø	L	V.230 Watt
0650025A0075X	-	6.5 mm	25 mm	75	0650080A0200X	0650080B0200X	6.5 mm	80 mm	200
0650025A0100X	-	6.5 mm	25 mm	100	0650080A0250X	0650080B0250X	6.5 mm	80 mm	250
0650025A0150X	-	6.5 mm	25 mm	150	0650080A0300X	0650080B0300X	6.5 mm	80 mm	300
0650025A0175X	-	6.5 mm	25 mm	175	0650100A0125X	-	6.5 mm	100 mm	125
0650040A0100X	-	6.5 mm	40 mm	100	0650100A0150X	-	6.5 mm	100 mm	150
0650040A0125X	0650040B0125X	6.5 mm	40 mm	125	0650100A0200X	-	6.5 mm	100 mm	200
0650040A0150X	0650040B0150X	6.5 mm	40 mm	150	0650100A0250X	0650100B0250X	6.5 mm	100 mm	250
0650040A0175X	0650040B0175X	6.5 mm	40 mm	175	0650100A0300X	0650100B0300X	6.5 mm	100 mm	300
0650040A0200X	0650040B0200X	6.5 mm	40 mm	200	0650100A0350X	-	6.5 mm	100 mm	350
0650040A0250X	-	6.5 mm	40 mm	250	0650100A0400X	0650100B0400X	6.5 mm	100 mm	400
0650050A0125X	-	6.5 mm	50 mm	125	0650130A0125X	-	6.5 mm	130 mm	125
0650050A0150X	0650050B0150X	6.5 mm	50 mm	150	0650130A0150X	-	6.5 mm	130 mm	150
0650050A0175X	0650050B0175X	6.5 mm	50 mm	175	0650130A0200X	-	6.5 mm	130 mm	200
0650050A0200X	0650050B0200X	6.5 mm	50 mm	200	0650130A0250X	-	6.5 mm	130 mm	250
0650050A0250X	0650050B0250X	6.5 mm	50 mm	250	0650130A0300X	-	6.5 mm	130 mm	300
0650060A0125X	-	6.5 mm	60 mm	125	0650130A0350X	-	6.5 mm	130 mm	350
0650060A0150X	-	6.5 mm	60 mm	150	0650130A0400X	-	6.5 mm	130 mm	400
0650060A0175X	-	6.5 mm	60 mm	175	0650160A0150X	-	6.5 mm	160 mm	150
0650060A0200X	0650060B0200X	6.5 mm	60 mm	200	0650160A0200X	-	6.5 mm	160 mm	200
0650060A0250X	0650060B0250X	6.5 mm	60 mm	250	0650160A0300X	-	6.5 mm	160 mm	300
0650060A0300X	0650060B0300X	6.5 mm	60 mm	300	0650160A0350X	-	6.5 mm	160 mm	350
0650080A0125X	-	6.5 mm	80 mm	125	0650160A0400X	-	6.5 mm	160 mm	400
0650080A0175X	-	6.5 mm	80 mm	175	0650160A0500X	-	6.5 mm	160 mm	500